MODULAR ICE CUBE MACHINE

ICETRO

SCI-200A(D, H)



W x D x H inch(mm)

30"(762) x 24"(610) x 23"(580)

Feature

- 510 lbs(231 kg) daily Ice production
- Storage Bin Option : IBS-316(353 lbs / 160 kg) & IBS-320(441 lbs / 200 kg)
- Stackable SCI-200A or SCI-300A
- Space saving solution with Powerful Performance
- Designed for easy installation and service
- Easy access to food zone with removal of two screws
- Easy cleaning by Clean switch and Plastic food zone
- Easy maintenance by quick disassembling
- Power switch accessible without panel removal
- Simple control, convenient, reliable and long lasting
- Easy to check Power/Full Ice/ Error with Display Lamp
- High reliability and low maintenance expense
- High density urethane foaming insulation keeps higher rigidity of the ice
- Includes ice scoop and 10ft power cable
- 304 Durable Stainless steel Construction
- Three ice sizes to choose from Regular, Dice and Half Dice
- R-404A Refrigerant


Dimensions

Dimensions	Net	Gross
Width	30"(762 mm)	32"(825 mm)
Depth	24"(610 mm)	27"(675 mm)
Height	23"(580 mm)	30"(765 mm)
Weight	141 lbs(64 kg)	170 lbs(77 kg)


Operating Limits

Ambient Temp Range	10 ~ 38 ℃ (50 ~ 100 ℉)
Water Temp Range	10 ~ 32 ℃ (50 ~ 90 ℉)
Water Pressure	20 ~ 80 psi (1.38 ~ 5.52 bar)
Voltage Range	±10% from regular voltage


Ice Dimension



REGULAR
29 x 29 x 22 (mm)
1⅛ x 1⅛ x ⅞ (inch)



DICE
22 x 22 x 22 (mm)
⅞ x ⅞ x ⅞ (inch)



HALF DICE
9.5 x 29 x 22 (mm)
⅜ x 1⅛ x ⅞ (inch)


Certification

CE NSF ETL US Intertek ETL Intertek UL LISTED KC ISO 9001 SASO


ICETRO
7, GEOMDAN-RO 54BEON-GIL, SEO-GU, INCHEON, KOREA
• TEL : +82-32-814-2160 Ext. 210, 220 • FAX : +82-32-814-1798
• WEB : www.icetro.com • E-mail : sales@icemaker.co.kr

Dimension – Unit : mm (inch)


[USA 220V/60Hz/1PH Model]



FRONT



SIDE



BACK


Specification

Model	Condenser	Ice Type	Ice Production 24 Hours		Power Consumption	Electrical Option	Water Usage gal/100 lbs. @90˚/70˚F (32˚/21˚C)	Power kWh/100 lbs. @90˚/70˚F (32˚/21˚C)	BTUs per hour
			Air/Water 21℃(70˚F)/10℃(50˚F)	Air/Water 32℃(90˚F)/21℃(70˚F)					
SCI-200A	Air-Cooled	REGULAR	510 lbs(231 kg)	441 lbs(200 kg)	1,250 W(±10 %)	208~230V/60Hz/1PH 220~240V/50Hz/1PH 115V/60Hz/1PH	19	6.19	5,200
SCI-200AD		DICE							
SCI-200AH		HALF DICE							

Detail View



Easy to check and control by the front display



Storage Bin Option :
IBS-316(353 lbs / 160 kg)
IBS-320(441 lbs / 200 kg)



Rear In / Both Side Out Air flow

※ Design and Specification are subject to change without notice.

ICETRO
7, GEOMDAN-RO 54BEON-GIL, SEO-GU, INCHEON, KOREA
• TEL : +82-32-814-2160 Ext. 210, 220 • FAX : +82-32-814-1798
• WEB : www.icetro.com • E-mail : sales@icemaker.co.kr