

Take the Lead

Ice Cube Machine


Self-Contained Type

Modular Type
Flake Ice & Nugget Ice Machine
Remote Condenser Ice Machine
Storage Bin Options

Ice Dispenser Snow Flake Ice Machine



SELF-CONTAINED TYPE





A25B15

MODEL	STORAGE CAPACITY		DIMENSIO	DIMENSION (WxDxH)			ICE SHAPE
WIODEL			mm inch				ICE SHAFE
A25B15	12	12 26 380 x 64		15 x 26 x 34	47	104	GOURMET
CONDENSER	ELECTRICAL OPTIONS		POWER Air / Water CONSUMPTION 21°C(70°F) /10°C(50°F)		Air / Wate 32°C(90°F) /21°		
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph		500W	31Kg (68.34lbs)	27Kg (59.5		2lbs)



SCI-035

MODEL		RAGE ACITY	DIMENSIO	N (WxDxH)	WEI	ICE SHAPE	
MODEL			mm inch				ICLSHAFE
SCI-035	13 29		407 x 463 x 770	16 x 18 x 31	39	85	GOURMET
CONDENSER	ELECTRICAL OPTIONS		POWER Air / Water CONSUMPTION 21°C(70°F) /10°C(50°F)		32	Air / Wat °C(90°F) /21	
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph		450W	36Kg (79.36lbs)	26Kg (57.32		2lbs)



SCI-050

MODEL		RAGE ACITY	DIMENSIO	DIMENSION (WxDxH)			ICE SHAPE
SCI-050	25 55		524 x 642 x 908	21 x 26 x 36	51	111	GOURMET
CONDENSER	ELECTRICAL OPTIONS		POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)	Air / Water 32°C(90°F) /21°C		
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph		800W	58Kg (127.86lbs)	43Kg (94.79lt		9lbs)



SCI-090

ı	MODEL		RAGE ACITY	DIMENSIO	N (WxDxH)		GHT ET)	ICE SHAPE
ı				mm inch				IOL SHAFE
	SCI-090	55	122	754 x 655 x 1133 30 x 26 x 45		85	187	GOURMET
	CONDENSER		TRICAL TIONS	POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)			
	Air Cooled	208~230\	0Hz/1Ph V/60Hz/1Ph V/50Hz/1Ph	1100W	97Kg (213.84lbs)	79Kg (174.1		6lbs)




SCI-120A

MODEL		RAGE ACITY	DIMENSIO	WEI (N	ICE SHAPE		
MODEL		lb	mm		kg	lb	IOL SHAFE
SCI-120A	55 122		755 x 646 x 1137	30 x 26 x 45	89	196	GOURMET
CONDENSER		TRICAL TIONS	POWER Air / Water CONSUMPTION 21°C(70°F) /10°C(50°F)		Air / Wa 32°C(90°F) /21		
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph		1400W	112Kg (246.91lbs)	95Kg (209.43		13lbs)

^{*} Design and Specification are subject to change without notice.

SELF-CONTAINED TYPE









ICI-050V(H)(F)

MODEL		RAGE ACITY	DIMENSIO	N (WxDxH)	WEI (N	GHT ET)	ICE SHAPE
	kg	lb	mm	inch	kg	lb	
ICI-050V(F)	12	27	520 x 567 x 855	21 y 22 y 24	21 x 23 x 34 51		DICE
ICI-050VH(F)	12	21	520 X 507 X 855	21 X 23 X 34	51	112	SMALL HALF
CONDENSER		TRICAL TIONS	POWER Air / Water CONSUMPTION 21°C(70°F) /10°C(50°F)		32	Air / Wat °C(90°F) /21	
Air Cooled	208~230\	60Hz/1Ph //60Hz/1Ph //50Hz/1Ph	500W	54Kg (119.04lbs) – DICE 55Kg (121.25lbs) - HALF	42Kg (92.59lbs 44kg (97lbs) - SN		,

* F: Optional Carbon Water Filter

ICI-120VAD(H)S



MODEL		STORAGE CAPACITY		DIMEN	DIMENSION (WxDxH)			ICE SHAPE
		kg	lb	mm inch		kg	lb	
ICI-120VA	.DS	35	77	660 x 694 x 963 26 x 28 x 38		CC0C0.40C0		DICE
ICI-120VA	ICI-120VAHS		77	660 X 694 X 963	26 X 28 X 38	73	161	HALF
CONDENSER	CONDENSER			POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)	32	Air / Wat 2°C(90°F) /21	
Air Cooled	Air Cooled 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph			480W 550W	480W 119Kg (262.35lbs)		89Kg (196.2	21lbs)


ICI-120VAD(H)L



MODEL			RAGE ACITY	DIMEN	NSIO	N (WxDxH)	WEI (NI		ICE SHAPE
		kg	lb	mm	mm inch		kg	lb	
ICI-120VA	ADL	60	133	660 x 694 x 1113 26 x 28 x 44		78 172		DICE	
ICI-120VA	.HL	00 133		000 x 094 x 1113		20 X 28 X 44	78	172	HALF
CONDENSER		ELECTRICAL OPTIONS		POWER CONSUMPTION 2		Air / Water 21°C(70°F) /10°C(50°F)	32	Air / Wat °C(90°F) /21°	
Air Cooled		·230V/60H; ·240V/50H;		480W 550W		119Kg (262.35lbs)		89Kg (196.2	21lbs)

^{*} Design and Specification are subject to change without notice.

MODULAR TYPE











MODEL	STOF CAPA		DIMENSION (WxDxH)		WEIGHT (NET)		ICE SHAPE
	kg	lb	mm	inch	kg	lb	
IM-220AD	Storage B		F60 v 620 v F72	22 2 24 0 2 22 6	6.5	1.40	DICE
IM-220AH	IBS-210/ (100kg/221lbs)		560 x 630 x 573	22 x 24.8 x 22.6	65	143	HALF
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)		Air / Water 32°C(90°F) /21°C(70°F)		
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph		201Kg (443lbs)	148Kg (326lbs)		

IM-260AD(H, R)



MODEL	STOF CAPA	RAGE CITY	DIMENSIO	N (WxDxH)	WEI (NI	GHT ET)	ICE SHAPE
	kg lb		mm	inch	kg	lb	
IM-260AR	Ctorogo D	in Ontion					REGULAR
IM-260AD	Storage B IBS-316/	IBS-320	762 x 630 x 573	30 x 24.8 x 22.6	79	174	DICE
IM-260AH	(160kg/353lbs)	(ZUUKG/44 IIDS)					HALF
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	Air / \ 21°C(70°F) .		32	Air / \ 2°C(90°F)	Water /21°C(70°F)
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	1000W	272Kg (600lbs)	215Kg (474lbs)		(474lbs)

IM-350AD(H, R)



MODEL		RAGE ACITY	DIMENSIO		GHT ET)	ICE SHAPE	
		lb		inch	kg		
IM-350AR	Ctorogo F	lin Ontion					REGULAR
IM-350AD	Storage E IBS-316/	'IBS-320	762 x 630 x 573	30 x 24.8 x 22.6	85	187	DICE
IM-350AH	(160kg/353lbs)	(200kg/441lbs)					HALF
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	Air / \ 21°C(70°F) .		32		Water /21°C(70°F)
Air Cooled	208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	1590W	324Kg (714lbs)		236Kg (520lbs)		(520lbs)

IM-500AD(H, R)



MODEL	STOF CAPA	RAGE CITY	DIMENSIO	WEIGHT (NET)		ICE SHAPE	
	kg lb		mm	inch	kg	lb	
IM-500AR	Ctorogo P	in Ontion					REGULAR
IM-500AD	Storage B IBS-316/	IBS-320	762 x 630 x 770	30 x 24.8 x 30.3	105	231	DICE
IM-500AH	(160kg/353lbs)ı	(200kg/44 fibs)					HALF
CONDENSER	ELECTRICAL POWER OPTIONS CONSUMPTION		Air / Water 21°C(70°F) /10°C(50°F)		Air / \ 32°C(90°F) .		
Air Cooled	208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	1839W	501Kg (⁻	1105lbs)	396Kg (873lbs)		(873lbs)

^{*} Design and Specification are subject to change without notice.

REMOTE CONDENSER ICE MACHINE



TUBE-IN 1/2" / 6m / 3kg (6.6lbs)

* Please note that the tubes are option.



TUBE-OUT 3/8" / 6m / 3kg (6.6lbs)



IM-500R



IM-500RD

IM-500RD(H, R) / IM-500R

MODEL	STORAGE	CAPACITY	DIMENSIO	N (WxDxH)	WEIGH	T(NET)	— ICE SHAPE
MODEL	kg	lb	mm	inch	kg	lb	- ICL SHAFE
IM-500RR	Ctarage	Dia Ontion					REGULAR
IM-500RD	IBS-316,	Storage Bin Option IBS-316/IBS-320 (160kg/353lbs)(200kg/441lbs)		30 x 24.8 x 30.3	93	205	DICE
IM-500RH	(TOUKG/353IDS)	((200kg/441lbs)					HALF
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)		3	Air / Water 32°C(90°F) /21°C(70°F)	
REMOTE	208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	1800W	501Kg (1105lbs)	396Kg (873lbs)		Blbs)
MODEL	DESCRIPTION	DISTADISTANCE(MAX.)NCE(MAX.)	DIMENSIO				ET)
MODEL		DISTADISTANOE(NIAX.)NOE(NIAX.)					lb
IM-500R	IM-500RD(H, R) REMOTE CONDENSER	30M	574 x 898 x 688	23 x 35 x 27	35		76

^{*} Design and Specification are subject to change without notice.

FLAKE ICE & NUGGET ICE MACHINE

- ✓ 22" SLIM DESIGN
- ✓ ADOPTED SLEEVE BEARING FOR HYGIENE IMPROVEMENT
- ✓ SELECTABLE CHOICE FLAKE OR NUGGET TYPE





FLAKE CUTTER

NUGGET CUTTER



IFI-770F(N)



FLAKE EXTRUDING HEAD



NUGGET EXTRUDING HEAD





IFI-770F(N)

MODEL	STORAGE CAPACITY		DIMENSION (WxDxH)		WEIG ¹	T(NET)	ICE SHAPE	
MODEL	kg	kg lb		inch	kg	lb	Opti	
IFI-770F(N)	Storage B IBS-210(100kg/221lbs)/		560 x 645 x 660 22 x 25 x 26		83	183	FLAKE	NUGGET
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	21	Air / Water °C(70°F) /10°C(50°F))	Air / Water 32°C(90°F) /21°C(70°F)		
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	1200W		g (727.52lbs) – FL/ (692.25lbs) – NUG		290Kg (639.34lbs) – FLAKE 288Kg (634.93lbs) – NUGGE		

^{*} Design and Specification are subject to change without notice.

STORAGE BIN OPTIONS



IBS-210

MODEL	APPLICABLE		STORAGE CAPACITY		DIMENSIO			
WIODEL		lb	kg	lb	mm	inch		lb
IBS-210	IM-220 IFI-77	DAD(H) OF(N)	100	220	568 x 870 x 869 (Without legs)	22 x 34 x 34 (Without legs)	35	77



IBS-212

MODEL	APPLICABLE		STORAGE CAPACITY		DIMENSIO	WEIGHT		
MODEL	kg	lb	kg	lb	mm	inch	kg	lb
IBS-212	IM-22 IFI-77	0AD(H) 70F(N)	120	265	568 x 870 x 969 (Without legs)	22 x 34 x 38 (Without legs)	45	99



IBS-316

MODEL		CABLE	STORAGE CAPACITY		DIMENSIO			
WIODEL	kg	lb	kg	lb	mm	inch	kg	lb
IBS-316	IM-350/ IM-500/	AD(H, R) AD(H, R) AD(H, R) RD(H, R)	160	353	768 x 870 x 969 (Without legs)	30 x 34 x 38 (Without legs)	55	121



IBS-320

MODEL	APPLICABLE		STORAGE CAPACITY		DIMENSIO	WEIGHT		
MODEL		lb	kg	lb	mm	inch	kg	lb
IBS-320	IM-350A IM-500A		200	441	768 x 870 x 1169 (Without legs)	30 x 34 x 46 (Without legs)	65	143

* Design and Specification are subject to change without notice.

DISPENSER ICE MACHINE



- One touch detachable cover

- Setting buttons located in front

ID-070AN

MODEL	STORAGE	CAPACITY	DIMENSIO	WEI	GHT	IOE OLIABE		
MODEL	kg	lb	mm inch		kg lb		ICE SHAPE	
ID-070AN	2.4	5.3	350 X 605 X 590	13.7 X 23.8 X 23.2	46	101	NUGGET	
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)		Air / Water 32°C(90°F) /21°C(70°F)			
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	370W	65Kg (143lbs)	48Kg (1		106lbs)	

^{*} Design and Specification are subject to change without notice.

DISPENSER ICE MACHINE BUILT-In type. - Air In from Bottom - Air Out from Top THREE MODES available. - ICE/WATER/ICE & WATER selectable by touch buttons. **Optics Serving Antibacterial System** - Sterilize dispense chute and lever to eliminate possibility of bacteria **ID-150AN**

Easy & Efficient Service Availability

- Swing type front door
- Door open in front

ID-150AN

MODEL	STORAGE	CAPACITY	DIMENSIO	WEI	GHT	IOF OLLARS	
MODEL	kg	kg lb mm inch		kg	lb	ICE SHAPE	
ID-150AN	5	11	421 x 635 x 710(810)	16.5 x 25 x 28(31.8)	65	143	NUGGET
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION	Air / Water 21°C(70°F) /10°C(50°F)				
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	620W	135Kg	(298lbs)		107Kg	(236lbs)

 $[\]ensuremath{\,\%\,}$ Design and Specification are subject to change without notice.

DISPENSER ICE MACHINE



ID-200AN



BUILT-In type.

- Air In from Bottom
- Air Out from Top

THREE MODES available.

- ICE/WATER/ICE & WATER selectable by touch buttons.



Optics Serving Antibacterial System

- Sterilize dispense chute and lever to eliminate possibility of bacteria



Easy & Efficient Service Availability

- Swing type front door
- Door open in front


ID-200AN

MODEL	STORAGE	CAPACITY	DIMENSIC	WEI	GHT	IOF OLLAPS		
MODEL	kg	lb	mm inch				CE SHAPE	
ID-200AN	14	31	421 X 700 X 1050	16.5 X 27.5 X 341.3	75	165.3	NUGGET	
CONDENSER	ELECTRICAL OPTIONS	POWER CONSUMPTION						
Air Cooled	115V/60Hz/1Ph 208~230V/60Hz/1Ph 220~240V/50Hz/1Ph	620W	208Kg	208Kg (458lbs)		170Kg	(374lbs)	

^{*} Design and Specification are subject to change without notice.

SNOW FLAKE ICE MACHINE

- ✓ ADOPTED SOFT ICE CREAM TECHNOLOGY TO ICE MACHINE
- ✓ BEST DESIGN FOR HYGIENE IMPROVEMENT & EASY MAINTENANCE
- ✓ WORLD STANDARD OF SNOW FLAKE ICE MACHINE







IIS-320SA

MODEL	PRODUCTION (CAPACITY (MILK)	PRODUCTION CA	PRODUCTION CAPACITY (WATER) STO		STORAGE CAPACITY		DIMENSION (WxDxH)	
MODEL		lb	kg	lb	liter	gal	mm	inch	
IIS-320SA	460	1091	320	705	53	14	520 x 745 x 1405	21 x 30 x 56	
CONDENSER	FI FCTRICA	ELECTRICAL OPTIONS P		POWER CONSUMPTION -		WEIGHT			
CONDENSER									
Air Cooled	208~230V	//60Hz/1Ph	1940\\	1840W (Max)		150		335	
All Cooled	220~240V	//50Hz/1Ph	10400	(IVIAX)	152			333	

^{*} Design and Specification are subject to change without notice.



Pride of No.1 brand in Korea

We are committed to providing first-class equipment and excellent customer service.

The ICETRO brand stands for the best quality and the best value-it is our platform and we will strive to continue upward in making it a true brand name around the world.

"The best value of soft serve ice cream machine, slush machine and ice maker"

















SINCE 1981 - ARTISAN SPIRIT

Ice Cube Machine Ice Cream Machine Slush Machine

54-7 Road, Gumdan-Ro, Seo-ku, Incheon, Korea TEL: +82-32-814-2160 FAX: +82-32-814-1798

Website: www.icetro.com E-mail:sales@icemaker.co.kr

Distributed	hv
DISHIDUICA	IJV

Distributed by .			